Metadata

| | <u> </u> |
|------------------------------------|--|
| Standardized Instrument Name | METEOROLOGICAL STATIONS |
| Scheme URI | http://vocab.nerc.ac.uk/collection/P19/current/PLSR0226/ |
| Term URI | SDN:P19::PLSR0226 |
| Instrument DOI | |
| Instrument Unique ID | 30023406813390 |
| ID Type | Serial Number |
| Model No. | H22-E14, SOH118303 |
| Instrument Type | Baseline |
| Description | Made up of multiple components listed below. Serial number is Iridium Weather station IMEI Equipment cost: \$9,904.50 + Iridium satellite Premium Plan: \$1,350 Sensor details found in attachment - Instrument Details - HOBO MMF Weather Station 1 |
| Manufacturer | Hoskin Scientific Limited |
| Manufacturer type | Organizational |
| Notes | HOBO brand field gear that includes various sensors attached to tripod outfitted with solar panel and battery located in housing box. This meteorological station is located in St. Laurent and is owned by the Manitoba Métis Federation (MMF). Calibration certificates stored in Lab Collector. They can be provided upon request. Site is currently decommissioned due to sensor and battery failure. Archived data collected prior to decommissioning will be made available. When active again, link to dataset page of station will be placed here. |
| Sensor Details | |
| Sensor Details 1 | |
| Instrument Sensor Name | Temperature and Relative Humidity |
| Instrument Sensor Serial No. | 21048243 |
| Sensor Range | Temperature: -40°C to 75°C (-40°F to 167°F); RH: 0-100% RH at -40° to 75°C (-40° to 167°F); exposure to conditions below -20°C (-4°F) or above 95% RH may temporarily increase the maximum RH sensor error by an additional 1% |
| Sensor Sensitivity | Temperature: ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F); RH: ±2.5% from 10% to 90% RH typical to a maximum of ±3.5% including hysteresis at 25°C (77°F); below 10% and above 90% ±5% typical |
| Sensor Units | °C and % |
| Last Calibration Date | |
| Sensor Details 2 | |

Instrument Photosynthetically Active Radiation (PAR) Sensor Name Instrument 21040570 Sensor Serial No. 0 to 2500 μ mol/m2/sec, wavelengths 400 to 700 nm Sensor Range ±5 μmol/m2/sec or ± 5%, whichever is greater in sunlight; additional temperature induced error Sensor ±0.75 μmol/m2/sec/°C from 25°C (0.42 μmol/m2/sec/°F from 77°F) Sensitivity Sensor Units µmol/m2/sec Last Calibration Date Sensor Details 3 Instrument **Barometric Pressure** Sensor Name Instrument Sensor Serial 20812842 No. Sensor Range Rated for -40C to +70C, must be used inside logger case, w/ 10 cm cable Sensor ±3.0 mbar (0.088 in. Hg) over full pressure range at 25°C (77°F); maximum error of ±5.0 mbar (0.148 in. Hg) over -40° to 70°C (-40° to 158°F) Sensitivity Sensor Units mbar **Last Calibration** Date Sensor Details 4 Instrument Wind sensor/monitor Sensor Name Instrument Sensor Serial 21055171 Sensor Range S-WCB-M003: 0 to 50 m/s (0 to 112 mph) Sensor 0.20 m/s (0.46 mph) and 1.4 degrees Sensitivity Sensor Units m/s and degrees **Last Calibration** Date Sensor Details 5 Instrument Rain Gauge Sensor Name Instrument Sensor Serial 21050257 No. 0 to 12.7 cm (0 to 5 in.) per hour, maximum 4000 tips per logging interval Sensor Range Sensor 0.01 in. (S-RGA-M002) or 0.2 mm (S-RGB-M002) Sensitivity Sensor Units mm

Last Calibration

Date

Related Datasets

Title St Laurent Li Taan Aen Staansyoon_17060

URL https://canwin-datahub.ad.umanitoba.ca/data/en/dataset/stlaurent-metdata_17060